

## **MOSIL SPRAY - 923**

### **Dry Corrosion Protection Spray**

SPRAY - 923 is a dry corrosion protection spray for long term indoor and outdoor protection of components and equipments from rust and corrosion. It is ideally suitable for long periods of storage such as in moulding die, precision equipment components etc. A uniformly sprayed surface component is observed with a dry film that has an excellent resistance to humidity and corrosive atmosphere which provides protection for a period of more than 30 months.

#### **AREA OF APPLICATION**

1. Protection of finished components, in-process parts, in-transit goods, raw materials, structural steel.
2. Effective corrosion shield for overseas shipments, winterizing of farm machinery outdoor storage.
3. Protection of equipment, tools, dies, molds, jigs, pipes, shafts, housings, wire ropes, valves, gears.
4. To be used for brine and chloride resistance in refrigeration plants.
5. In paper and pulp plants.
6. As a cable end sealer and pipe joint protector in utilities.
7. Protection of air conditioning and electrical equipment in hospitals and educational institutions

**PACKING:** 500ml Eco-friendly Aerosol Spray

Owing to evolving packaging solutions, user is requested to kindly check the availability of a specific pack size prior to standardization.

#### **Mosil Lubricants Private Limited**

Technical Services Dept: "ANIRA" Plot No. A-791/3, MIDC Khairne, Navi Mumbai - 400710. INDIA  
T: +91 22 2464 0500 /0501 | F: +91 22 2778 8505 | E: corporate@mosil.com | W: www.mosil.com  
Regd Office: 166/1, KALANIDHI, Sion(West), Mumbai - 400 022 | CIN # U23200 MH 2000 PT C124177



<u>CHARACTERISTICS</u>	<u>TYPICAL VALUES</u>
1. Appearance	Dry Glossy Film
2. Color	Clear
3. Specific Gravity @ R. T.	0.75 - 0.85
4. Odor	Faint
5. Drying Time for handling	20 - 30 minutes
6. Film Type	Dry
7. Temperature Range	-40 to 100°C
8. Propellant	Non CFC Type, Eco-friendly
9. Container	Aerosol tin with 25mm valve and actuator

*Material Safety Information required for safe usage of this product may not be included in this product bulletin and may be sought by contacting MOSIL. Users are advised to go through the Material Safety Data Sheet (MSDS) of this product prior to application / usage of this product.*

*All statements and information contained in this document are based on the laboratory testing and user experience on actual applications. Owing to the exhaustive possibility of application for which this product may be used and the variety of equipments, performance parameters, environmental conditions and unpredictable human factors, we strongly recommend that this product be tested on the actual application prior to its standardization. All information contained herewith is offered in good faith but without any expressed or implied warranty. This Product Bulletin may already have been revised considering the availability of raw components, legislation, user experience & expectations and enhancement of knowledge of the development team of MOSIL. Users are requested to kindly seek the latest version of this product bulletin by contacting MOSIL. Information provided in this Product Bulletin is based on the generalised expectations and requirements of users. Additional information for this product may also be sought by contacting MOSIL.*

Rev 00, Issue 00

**Mosil Lubricants Private Limited**

**Technical Services Dept:** "ANIRA" Plot No. A-791/3, MIDC Khairne, Navi Mumbai - 400710. INDIA  
T: +91 22 2464 0500 /0501 | F: +91 22 2778 8505 | E: corporate@mosil.com | W: www.mosil.com  
Regd Office: 166/1, KALANIDHI, Sion(West), Mumbai - 400 022 | CIN # U23200 MH 2000 PT C124177

